


PRODUCT-DETAILS

GSC415

2-PC OUTER SLV CONN BLUE I.D. 0.415



General Information

Extended Product Type	GSC415
Product ID	7TAI029070R0058
EAN	5414363114598
Catalog Description	2-PC OUTER SLV CONN BLUE I.D. 0.415
Long Description	Two Piece Outer Sleeve Connector for Hexagonal Range, Length 6.4mm, Inner Diameter 10.54mm, Outer Diameter 11.76mm, Color Blue, Soft Bronze, Tin Plated

Ordering

EAN	5414363114598
-----	---------------

Dimensions

Product Net Length	0, mm
--------------------	-------

Container Information

Package Level 1 Units	1000 piece
Package Level 1 Width	4.5 in 114 mm
Package Level 1 Height	3 in 76 mm
Package Level 1 Depth /	6 in

Length	152 mm
Package Level 2 Units	10000 piece
Package Level 2 Width	12.7 in 323 mm
Package Level 2 Height	3.5 in 89 mm
Package Level 2 Depth / Length	24.2 in 615 mm

Additional Information

Brand / Label	Sta-Kon
Color	Blue
Effective Date	19680516
Material	Soft Bronze
Number of Batteries	0
Product Name	STA-KON AND CATAMOUNT TERMINAL
Product Type	Two-Piece Outer Sleeve Connector
Special Functions	Shielded cable grounding system made of 2 cylindrical sleeves (inner sleeve + outer sleeve), for solderless crimp connection. Outer sleeve for the Hexagonal Range (the outer sleeve is crimped with a hand tool and the result is a hexagonal-shaped crimp), for grounding shielded and coaxial cables. The sleeves are color coded according to their size. Millions of installations in communications, aerospace, electronic, telephone, radio and TV applications.
UPC	786210814032

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	GSC415
Instructions and Manuals	GSC415

Classifications

ETIM 6	EC002650 - Connection for screened wires
ETIM 7	EC002650 - Connection for screened wires
UNSPSC	39121432
WEEE Category	Product Not in WEEE Scope
IDEA Granular Category Code (IGCC)	4603 >> Electrical terminals

Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Compression & Mechanical Connectors

