



## Main

|                              |                                                                  |
|------------------------------|------------------------------------------------------------------|
| Range of product             | TeSys                                                            |
| Device short name            | GV2DP                                                            |
| Product or component type    | Motor starter                                                    |
| Motor starter type           | Non reversing                                                    |
| Coordination type            | Type 2                                                           |
| Poles description            | 3P                                                               |
| Utilisation category         | AC-3                                                             |
| Motor power kW               | 0.06 kW at 400/415 V AC 50/60 Hz<br>0.06 kW at 440 V AC 50/60 Hz |
| [Uc] control circuit voltage | 230 V AC 50/60 Hz                                                |
| Magnetic tripping current    | 2.4 A                                                            |

## Complementary

|                                     |                                                                                                                                                        |
|-------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------|
| Device composition                  | 1 combination block GV2AF3<br>1 3-pole contactor<br>1 motor circuit breaker type GV2P                                                                  |
| Thermal protection adjustment range | 0.16...0.25 A                                                                                                                                          |
| Rated breaking capacity             | Iq 130 kA at 400/415 V conforming to IEC 60947-4-1<br>Iq 130 kA at 440 V conforming to IEC 60947-4-1<br>Iq 130 kA at 500 V conforming to IEC 60947-4-1 |
| Product weight                      | 0.686 kg                                                                                                                                               |
| Height                              | 176.4 mm                                                                                                                                               |
| Width                               | 45 mm                                                                                                                                                  |
| Depth                               | 105.6 mm                                                                                                                                               |

## Offer Sustainability

|                          |                                   |
|--------------------------|-----------------------------------|
| Sustainable offer status | Green Premium product             |
| REACH Regulation         | <a href="#">REACH Declaration</a> |
| EU RoHS Directive        | Compliant                         |

#### EU RoHS Declaration

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | Yes                                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a><br>Product out of China RoHS scope. Substance declaration for your information       |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | No need of specific recycling operations                                                                                    |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

#### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|