



Main

Range	TeSys
Device short name	GVAE
Product or component type	Auxiliary contact block
Product compatibility	GV2L GV2LE GV2ME GV2P GV2RT GV3L GV3P LS1D323
Pole contact composition	2 NO
Connections - terminals	Spring terminals 2 cable 0.75...1.5 mm²
Quantity per set	Set of 10

Complementary

Mounting location	Front side
[Ui] rated insulation voltage	300 V - conforming to CSA C22.2 No 14 250 V - conforming to IEC 60947-1 300 V - conforming to UL 508
[Ue] rated operational voltage	24...60 V DC 24...240 V AC
[Ith] conventional free air thermal current	2.5 A
Protection type	GB2CB06 circuit breaker <= 10 A GG fuse <= 10 A
Mechanical durability	100000 cycles
Rated operational power in VA	60 VA at 48 V AC-15 - electrical durability: 100000 cycles 48 VA at 24 V AC-15 - electrical durability: 100000 cycles 120 VA at 230...240 V AC-15 - electrical durability: 100000 cycles 120 VA at 110...120 V AC-15 - electrical durability: 100000 cycles
Rated operational power in W	9 W at 60 V DC-13 - electrical durability: 100000 cycles 24 W at 24 V DC-13 - electrical durability: 100000 cycles 15 W at 48 V DC-13 - electrical durability: 100000 cycles
Tightening torque	<= 1.4 N.m - on screw clamp terminals
Height	10 mm
Width	44.5 mm
Depth	15 mm

Environment

Environmental characteristic	Normal environment
------------------------------	--------------------