

PRODUCT-DETAILS

HAAM0404G1

1/2NPT NICKEL FLAMEPROOF FOR 20MM C



General Information

Extended Product Type	HAAM0404G1
Product ID	7TCA297090R0065
EAN	5011949016897
Catalog Description	1/2NPT NICKEL FLAMEPROOF FOR 20MM C
Long Description	Liquid Tight Fitting for Conduit, ATEX Flameproof G1 Gland, Straight with External Male Thread, Conduit Size 20mm, 1/2 Inch NPT Thread, CSA, Group I & II, Zones 1, 2, 21 and 22, Class I Div2 ABCD, Class II Div1 EFG, Nickel Plated Brass with Epoxy Resin Barrier

Additional Information

Application	Ideal for Ex I & II 2 GD Gas and Dust, Exde IIC and Exe II Applications
Product Type	Liquid Tight Conduit Fitting with Flameproof Barrier

Ordering

EAN	5011949016897
UPC	786210277189
Customs Tariff Number	7412200035

Technical

Number of Batteries	0
---------------------	---

Color	Metallic
Material	Brass with Epoxy Resin Barrier
Size	Conduit Size 20mm ; 1/2 Inch NPT Thread

Environmental

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Container Information

Package Level 1 Units	1 piece
Package Level 2 Units	50 piece
Package Level 2 Height	16 in 406 mm
Package Level 2 Depth / Length	14 in 356 mm
Package Level 2 Width	14 in 356 mm

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	HAAM0404G1
Instructions and Manuals	HAAM0404G1
Declaration of Conformity - CE	9AKK107492A9617

Classifications

UNSPSC	39121420
--------	----------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems

