



## PRODUCT-DETAILS

# HSB500-C

## SHRINK KON BOX - 6M TRANSP.



### General Information

|                       |                                                                                                            |
|-----------------------|------------------------------------------------------------------------------------------------------------|
| Extended Product Type | HSB500-C                                                                                                   |
| Product ID            | 7TCA017300R0366                                                                                            |
| EAN                   | 5414363104445                                                                                              |
| Catalog Description   | SHRINK KON BOX - 6M TRANSP.                                                                                |
| Long Description      | Thin Wall Heat Shrink Tubing in Dispenser Box - 1/2 Inch Expanded Inside Diameter - 6.0 Meters Transparent |

### Ordering

|     |               |
|-----|---------------|
| EAN | 5414363104445 |
|-----|---------------|

### Dimensions

|                    |                      |
|--------------------|----------------------|
| Product Net Weight | .502 lb<br>227.664 g |
|--------------------|----------------------|

### Container Information

|                        |                  |
|------------------------|------------------|
| Package Level 1 Units  | 1 piece          |
| Package Level 1 Width  | 2.4 in<br>61 mm  |
| Package Level 1 Height | 6.7 in<br>170 mm |

|                                |                   |
|--------------------------------|-------------------|
| Package Level 1 Depth / Length | 6.7 in<br>170 mm  |
| Package Level 2 Units          | 60 piece          |
| Package Level 2 Width          | 15.8 in<br>401 mm |
| Package Level 2 Height         | 22.5 in<br>572 mm |
| Package Level 2 Depth / Length | 20.9 in<br>531 mm |

## Additional Information

|                            |                                  |
|----------------------------|----------------------------------|
| Brand / Label              | Shrink-Kon                       |
| Color                      | Transparent                      |
| Dielectric Test Voltage    | 280/Mil (11kV/mm) V              |
| Flammability Hazard Rating | Self Extinguishing               |
| Number of Batteries        | 0                                |
| Process Temperature Rating | -67 to +212 °F<br>-55 to +100 °C |
| Product Name               | Plastic conduit                  |
| Product Type               | Thin-Wall Heat Shrinkable Tubing |
| Shrink Ratio               | 2:1                              |
| Shrink Temperature         | 230 °F<br>110 °C                 |
| Thickness                  | Thin                             |
| UPC                        | 786210564197                     |
| Water Absorption           | 0.03%                            |

## Certificates and Declarations (Document Number)

|                                   |          |
|-----------------------------------|----------|
| Data Sheet, Technical Information | HSB500-C |
| Instructions and Manuals          | HSB500-C |

## Classifications

|                                    |                              |
|------------------------------------|------------------------------|
| ETIM 6                             | EC000217 - Shrink tubing     |
| ETIM 7                             | EC000217 - Shrink tubing     |
| UNSPSC                             | 39121723                     |
| WEEE Category                      | Product Not in WEEE Scope    |
| IDEA Granular Category Code (IGCC) | 5073 >> Heat shrinkable tube |

## Categories

Low Voltage Products and Systems → Installation Products → Wire Management and Connectivity → Identification & Heat Shrink

