




Inductive tube sensor

I8-3020-BPKG/DY/AS-610-DPS

Status Archive

/I85008



- 1 Sensing face
- 2 LED operating status
- 3 LED switching status



Application

Operating principle	dynamic
---------------------	---------

Electrical data

Operating voltage [V]	10...35 DC
Current consumption [mA]	< 25
Protection class	III
Reverse polarity protection	yes

Outputs

Electrical design	PNP
Output function	normally open
Max. voltage drop switching output DC [V]	2
Permanent current rating of switching output DC [mA]	200
Short-circuit protection	yes
Overload protection	yes

Detection zone

Sensing range [mm]	< 20
Resolution of steel ball (diameter) [mm]	1
Max. part speed [m/s]	35



Inductive tube sensor

I8-3020-BPKG/DY/AS-610-DPS


Response times		
Pulse stretching	[ms]	100
Max. fall time	[ms]	100
Response time	[ms]	< 0.2
Operating conditions		
Ambient temperature	[°C]	-25...70
Protection		IP 67
Tests / approvals		
MTTF	[years]	982
Mechanical data		
Weight	[g]	30
Housing		rectangular
Dimensions	[mm]	70 x 20 x 12
Materials		housing: PC
Displays / operating elements		
Display	switching status	1 x LED, yellow
	operation	1 x LED, green
Accessories		
Accessories (supplied)		fixing straps: 2
Remarks		
Notes		discontinued article
Pack quantity		1 pcs.
Electrical connection - plug		
Connector: 1 x M8		
		



Inductive tube sensor

I8-3020-BPKG/DY/AS-610-DPS

Connection



Status Archive

/I85008