


IE5344



Inductive sensor

IEBC003BASKG/0,3M/AS



Electrical data

Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 10; (only in 3-wire operation)
Protection class		III
Reverse polarity protection		yes

Outputs

Electrical design		PNP/NPN
Output function		normally open
Max. voltage drop switching output DC	[V]	2.8
Minimum load current	[mA]	2
Max. leakage current	[mA]	0.5; (only in 2-wire operation)
Permanent current rating of switching output DC	[mA]	100; (only in 2-wire operation)
Switching frequency DC	[Hz]	1000
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

Detection zone

Sensing range	[mm]	3
Operating distance	[mm]	0...2.4

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.5 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	1...15

Operating conditions

Ambient temperature	[°C]	0...60
Protection		IP 67

IE5344



Inductive sensor

IEBC003BASKG/0,3M/AS

Tests / approvals		
EMC	EN 60947-5-2	
MTTF [years]	2988	
UL approval	Ta	-25...80 °C
	Enclosure type	Type 1
	voltage supply	Limited Voltage/Current
	File number UL	E174191

Mechanical data		
Weight [g]	24.2	
Housing	threaded type	
Mounting	flush mountable	
Dimensions [mm]	M8 x 1 / L = 37	
Thread designation	M8 x 1	
Materials	brass white bronze coated; sensing face: LCP	

Displays / operating elements		
Display	switching status	1 x LED, yellow

Electrical connection	
Connection	plug

Accessories	
Accessories (supplied)	lock nuts: 2

Remarks	
Pack quantity	1 pcs.

Electrical connection - plug

Cable: 0.3 m, PVC; 3 x 0.14 mm²

Connector: 1 x M8; Locking: snap-fit



IE5344



Inductive sensor

IEBC003BASKG/0,3M/AS

2-wire

