


IF6038



Inductive sensor

IFB3002-BPKG/V4A/0,4M/ZH



Electrical data

Operating voltage	[V]	10...30 DC
Current consumption	[mA]	< 15
Protection class		II
Reverse polarity protection		yes

Outputs

Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	1200
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

Detection zone

Sensing range	[mm]	2
Real sensing range S_r	[mm]	$2 \pm 10 \%$
Operating distance	[mm]	0...1.6

Accuracy / deviations

Hysteresis	[% of S_r]	1...15
Switch point drift	[% of S_r]	-10...10

Operating conditions

Ambient temperature	[°C]	-20...70
Protection		IP 67

Tests / approvals

EMC	EN 61000-4-2 ESD	4 kV CD / 8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-5 Surge	0,5 kV line to line, R_i : 2 Ohm
	EN 61000-4-6 HF conducted	10 V
	EN 55011 emission	class B
MTTF	[years]	3216

IF6038



Inductive sensor

IFB3002-BPKG/V4A/0,4M/ZH


Mechanical data		
Weight	[g]	20
Housing		threaded type
Mounting		flush mountable
Dimensions	[mm]	M12 x 1 / L = 31.5
Thread designation		M12 x 1
Materials		stainless steel; sensing face: PBT; lock nuts: stainless steel

Displays / operating elements		
Display	switching status	1 x LED, yellow

Remarks	
Pack quantity	1 pcs.

Electrical connection	
Cable: 0.4 m, PUR; 3 x 0.34 mm ²	

Connection



	Core colours :
BN =	brown
BU =	blue
BK =	black

Connector: 1 x flat-pin connector (4.8 x 0.5 mm)