




Inductive sensor

IGA3005-BPKG/US-104



Electrical data

Operating voltage	[V]	10...36 DC
Current consumption	[mA]	15; (24 V)
Protection class		II
Reverse polarity protection		yes

Outputs

Electrical design		PNP
Output function		normally open
Max. voltage drop switching output DC	[V]	2.5
Permanent current rating of switching output DC	[mA]	250
Switching frequency DC	[Hz]	500
Short-circuit protection		yes
Type of short-circuit protection		pulsed
Overload protection		yes

Detection zone

Sensing range	[mm]	5
Real sensing range Sr	[mm]	5 ± 10 %
Operating distance	[mm]	0...4.05

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / brass: 0.4 / aluminium: 0.3 / copper: 0.2
Hysteresis	[% of Sr]	1...15
Switch point drift	[% of Sr]	-10...10

Operating conditions

Ambient temperature	[°C]	-25...80
Protection		IP 67

IG5554



Inductive sensor

IGA3005-BPKG/US-104

Tests / approvals		
EMC	EN 60947-5-2	
MTTF	[years]	1884
UL approval	Ta	0...40 °C
	Enclosure type	Type 1
	voltage supply	Unlimited Voltage
	UL Approval no.	A004
	File number UL	E174191

Mechanical data		
Weight	[g]	73.8
Housing	threaded type	
Mounting	flush mountable	
Dimensions	[mm]	M18 x 1 / L = 89
Thread designation	M18 x 1	
Materials	brass white bronze coated; PC	

Displays / operating elements		
Display	switching status	1 x LED, yellow

Accessories		
Accessories (supplied)	lock nuts: 2	

Remarks		
Pack quantity	1 pcs.	

Electrical connection - plug

Connector: 1 x M12



IG5554

Inductive sensor

IGA3005-BPKG/US-104



Connection

