




Inductive sensor

IGB2008BAROG/UP/2LED/3M/PH



Electrical data

Operating voltage	[V]	10...36 DC
Protection class		II
Reverse polarity protection		no

Outputs

Electrical design		PNP/NPN
Output function		normally open
Max. voltage drop switching output DC	[V]	5
Minimum load current	[mA]	5
Max. leakage current	[mA]	1
Permanent current rating of switching output DC	[mA]	100
Switching frequency DC	[Hz]	100
Short-circuit protection		no
Overload protection		no

Detection zone

Sensing range	[mm]	8
Real sensing range Sr	[mm]	8 ± 10 %
Increased sensing range		yes

Accuracy / deviations

Correction factor		steel: 1 / stainless steel: 0.7 / aluminium: 0.4 / copper: 0.3
Hysteresis	[% of Sr]	3...15

Operating conditions

Ambient temperature	[°C]	-25...70
Protection		IP 67

Tests / approvals

EMC		EN 60947-5-2	
		EN 55011	class B
MTTF	[years]		1522


IG5820



Inductive sensor

IGB2008BAROG/UP/2LED/3M/PH

Mechanical data		
Weight	[g]	188.8
Housing		threaded type
Mounting		flush mountable
Dimensions	[mm]	M18 x 1 / L = 43
Thread designation		M18 x 1
Materials		brass white bronze coated; PBT
Displays / operating elements		
Display	switching status	1 x LED, red
	switching status	1 x LED, green
Optical setting aid		yes
Accessories		
Accessories (supplied)		lock nuts: 2
Remarks		
Notes		discontinued article
Pack quantity		1 pcs.
Electrical connection		
Cable: 3 m, PUR / PVC; 2 x 0.50 mm ²		
Connection		



Core colours :

BK = black