

# K1B002NCH

cam stepping switch - 1 pole - 45° - 12 A - for Ø 22 mm



## Main

|                                             |                                                              |
|---------------------------------------------|--------------------------------------------------------------|
| Range of product                            | Harmony K                                                    |
| Product or component type                   | Complete cam switch                                          |
| Component name                              | K1                                                           |
| [Ith] conventional free air thermal current | 12 A                                                         |
| Product mounting                            | Front mounting                                               |
| Fixing mode                                 | Ø 22 mm hole                                                 |
| Cam switch head type                        | With front plate 45 x 45 mm                                  |
| Type of operator                            | Black handle, length = 35 mm                                 |
| Rotary handle padlocking                    | Without                                                      |
| Presentation of legend                      | With metallic legend, 1 - 2 black marking                    |
| Cam switch function                         | Stepping switch                                              |
| Return                                      | Without                                                      |
| Off position                                | Without Off position                                         |
| Poles description                           | 1P                                                           |
| Switching positions                         | Right: 0° - 45°                                              |
| IP degree of protection                     | IP65 conforming to NF C 20-010<br>IP65 conforming to IEC 529 |

## Complementary

|                                              |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|----------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Number of steps                              | 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| Switching angle                              | 45 °                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| [Ui] rated insulation voltage                | 690 V degree of pollution 3 conforming to IEC 60947-1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| [Ithe] conventional enclosed thermal current | 10 A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Rated operational power in W                 | 8300 W AC-21 / 400 V 3 phases conforming to IEC 947-3<br>600 W AC-3 / 230 V 1 phase conforming to IEC 947-3<br>4800 W AC-21 / 230 V 3 phases conforming to IEC 947-3<br>2200 W AC-23A / 690 V 3 phases conforming to IEC 947-3<br>2200 W AC-23A / 500 V 3 phases conforming to IEC 947-3<br>2200 W AC-23A / 400 V 3 phases conforming to IEC 947-3<br>1500 W AC-3 / 690 V 3 phases conforming to IEC 947-3<br>1500 W AC-3 / 500 V 3 phases conforming to IEC 947-3<br>1500 W AC-3 / 400 V 3 phases conforming to IEC 947-3<br>1500 W AC-3 / 400 V 1 phase conforming to IEC 947-3<br>1500 W AC-23A / 230 V 3 phases conforming to IEC 947-3<br>1100 W AC-3 / 230 V 3 phases conforming to IEC 947-3<br>10500 W AC-21 / 500...660 V 3 phases conforming to IEC 947-3 |
| [Ie] rated operational current AC            | 5.6 A at 230 V AC-23A 3 phases conforming to IEC 947-3<br>4.8 A at 400 V AC-23A 3 phases conforming to IEC 947-3<br>4.6 A at 230 V AC-3 3 phases conforming to IEC 947-3<br>3.8 A at 500 V AC-23A 3 phases conforming to IEC 947-3<br>3.3 A at 400 V AC-3 3 phases conforming to IEC 947-3<br>2.8 A at 690 V AC-23A 3 phases conforming to IEC 947-3<br>2.8 A at 500 V AC-3 3 phases conforming to IEC 947-3<br>1.8 A at 690 V AC-3 3 phases conforming to IEC 947-3<br>3 A at 230 V AC-15 conforming to IEC 947-5-1<br>2 A at 400 V AC-15 conforming to IEC 947-5-1<br>1 A at 500 V AC-15 conforming to IEC 947-5-1                                                                                                                                                |
| Electrical durability                        | 500000 cycles AC-3<br>500000 cycles AC-23<br>1000000 cycles AC-21<br>1000000 cycles AC-15                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

|                                        |                                                                                                                                 |
|----------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| Operating rate                         | 2.5 cyc/mn AC-3<br>2.5 cyc/mn AC-23<br>2.5 cyc/mn AC-21<br>8333 cyc/mn AC-15                                                    |
| Short-circuit current                  | 10000 A                                                                                                                         |
| Short circuit protection               | 16 A by cartridge fuse, type gG                                                                                                 |
| [Uimp] rated impulse withstand voltage | 6 kV conforming to IEC 947-1<br>4 kV in isolating function                                                                      |
| Contacts operation                     | Slow-break                                                                                                                      |
| Positive opening                       | With                                                                                                                            |
| Electrical connection                  | Captive screw clamp terminals solid, 1 x 2.5 mm <sup>2</sup><br>Captive screw clamp terminals flexible, 2 x 1.5 mm <sup>2</sup> |
| Mechanical durability                  | 1000000 cycles                                                                                                                  |
| CAD overall width                      | 45 mm                                                                                                                           |
| CAD overall height                     | 50 mm                                                                                                                           |
| CAD overall depth                      | 49 mm                                                                                                                           |
| Product weight                         | 0.135 kg                                                                                                                        |

## Environment


|                                            |                                                                                                                                                            |
|--------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                                  | IEC 60947-5-1 for control circuit<br>IEC 60947-3 for power circuit<br>EN 60947-5-1 for control circuit<br>EN 60947-3 for power circuit<br>CENELEC EN 50013 |
| Product certifications                     | UL 240 V 0.33 hp 1 phase 2 -pole(s)<br>UL 240 V 1 hp 3 phases<br>CSA 240 V 3 hp 3 phases 2 -pole(s)<br>CSA 240 V 1 hp 1 phase                              |
| Protective treatment                       | TC                                                                                                                                                         |
| Ambient air temperature for operation      | -25...55 °C                                                                                                                                                |
| Ambient air temperature for storage        | -40...70 °C                                                                                                                                                |
| Shock resistance                           | 30 gn conforming to IEC 68-2-27                                                                                                                            |
| Vibration resistance                       | 5 gn, 10...150 Hz conforming to IEC 68-2-6                                                                                                                 |
| Class of protection against electric shock | Class II conforming to NF C 20-030<br>Class II conforming to IEC 536                                                                                       |

---

Operating Head and Body with Plastic Base

---

Front Mounting by  $\varnothing 22$  mm/0.87 in. Hole




a1 70.5 mm/2.78 in.

e support panel thickness 1 mm to 6 mm./0.039 in. to 0.24 in.


Link Positions (Factory Mounted)

Diagram for 2 to 5-step Stepping Switches


Select the number of steps according to the product characteristics.



Marking




Angular Position of Switch



Switching Program

Diagram for 2 to 5-step Stepping Switches

Select the number of steps according to the product characteristics.



Convention Used for Switching Program Representation

- ☒ Contact closed
- ☒ Contact closed in 2 positions and maintained between the 2 positions
- ☒ Sealed assembly for auto-maintain control
- ☒ Overlapping contacts

 Spring return position: for a switching angle of  $90^\circ$ , spring return is over  $30^\circ$  after the last position (for a maximum of 3 simultaneous contacts).

Example:

