



Main

Range of product	Harmony K
Product or component type	Complete cam switch
Component name	K2
[I _{th}] conventional free air thermal current	20 A
Product mounting	Front mounting
Fixing mode	Ø 22 mm hole
Cam switch head type	With front plate 45 x 45 mm
Type of operator	Black handle, length = 35 mm
Rotary handle padlocking	Without
Presentation of legend	With metallic legend, 0 - 1 black marking
Cam switch function	Switch
Return	Without
Off position	With Off position
Poles description	2P
Switching positions	Right: 0° - 90°
IP degree of protection	IP65 conforming to NF C 20-010 IP65 conforming to IEC 529

Complementary

Switching angle	90 °
[U _i] rated insulation voltage	690 V degree of pollution 3 conforming to IEC 60947-1
[I _{the}] conventional enclosed thermal current	16 A
Rated operational power in W	8000 W AC-21 / 230 V 3 phases conforming to IEC 60947-3 5500 W AC-23A / 690 V 3 phases conforming to IEC 60947-3 5500 W AC-23A / 500 V 3 phases conforming to IEC 60947-3 5500 W AC-23A / 400 V 3 phases conforming to IEC 60947-3 4000 W AC-3 / 690 V 3 phases conforming to IEC 60947-3 4000 W AC-3 / 500 V 3 phases conforming to IEC 60947-3 4000 W AC-3 / 400 V 3 phases conforming to IEC 60947-3 4000 W AC-23A / 230 V 3 phases conforming to IEC 60947-3 2200 W AC-3 / 400 V 1 phase conforming to IEC 60947-3 2200 W AC-3 / 230 V 3 phases conforming to IEC 60947-3 17000 W AC-21 / 500...660 V 3 phases conforming to IEC 60947-3 14000 W AC-21 / 400 V 3 phases conforming to IEC 60947-3 1300 W AC-3 / 230 V 1 phase conforming to IEC 60947-3
[I _e] rated operational current AC	8.9 A at 500 V AC-23A 3 phases conforming to IEC 60947-3 8.3 A at 230 V AC-3 3 phases conforming to IEC 60947-3 6.5 A at 500 V AC-3 3 phases conforming to IEC 60947-3 6.4 A at 690 V AC-23A 3 phases conforming to IEC 60947-3 4.7 A at 690 V AC-3 3 phases conforming to IEC 60947-3 14.6 A at 230 V AC-23A 3 phases conforming to IEC 60947-3 10.8 A at 400 V AC-23A 3 phases conforming to IEC 60947-3 8 A at 400 V AC-3 3 phases conforming to IEC 60947-3 4 A at 230 V AC-15 conforming to IEC 60947-5-1 3 A at 400 V AC-15 conforming to IEC 60947-5-1 2 A at 500 V AC-15 conforming to IEC 60947-5-1
Electrical durability	600000 cycles AC-21 600000 cycles AC-15 200000 cycles AC-3 200000 cycles AC-23
Operating rate	8.333 cyc/mn AC-15 2.5 cyc/mn AC-3 2.5 cyc/mn AC-23 2.5 cyc/mn AC-21


Short-circuit current	10000 A
Short circuit protection	20 A by cartridge fuse, type gG
[Uimp] rated impulse withstand voltage	6 kV conforming to IEC 60947-1 4 kV in isolating function
Contacts operation	Slow-break
Positive opening	With
Electrical connection	Captive screw clamp terminals solid, 1 x 2.5 mm ² Captive screw clamp terminals flexible, 2 x 1.5 mm ²
Mechanical durability	1000000 cycles
CAD overall width	45 mm
CAD overall height	50 mm
CAD overall depth	49 mm
Product weight	0.15 kg

Environment

Standards	IEC 60947-5-1 for control circuit IEC 60947-3 for power circuit EN 60947-5-1 for control circuit EN 60947-3 for power circuit CENELEC EN 50013
Product certifications	UL 240 V 0.33 hp 1 phase 2 -pole(s) UL 240 V 1 hp 3 phases CSA 240 V 3 hp 3 phases 2 -pole(s) CSA 240 V 1 hp 1 phase
Protective treatment	TC
Ambient air temperature for operation	-25...55 °C
Ambient air temperature for storage	-40...70 °C
Shock resistance	30 gn conforming to IEC 68-2-27
Vibration resistance	5 gn, 10...150 Hz conforming to IEC 68-2-6
Class of protection against electric shock	Class II conforming to NF C 20-030 Class II conforming to IEC 536

Operating Head and Body with Plastic Base

Front Mounting by $\varnothing 22$ mm/0.87 in. Hole




a1 70.5 mm/2.78 in.

e support panel thickness 1 mm to 6 mm./0.039 in. to 0.24 in.


Link Positions (Factory Mounted)

Diagram for 2 to 4-pole Switches

Select the number of poles according to the product characteristics.



Marking




Angular Position of Switch



Switching Program

Diagram for 2 to 4-pole Switches

Select the number of poles according to the product characteristics.



- (2) 2-pole
- (3) 3-pole
- (4) 4-pole

Convention Used for Switching Program Representation

- ☐
☒
Contact closed
- ☒
☒
Contact closed in 2 positions and maintained between the 2 positions
- ☒
☒
Sealed assembly for auto-maintain control
- ☒
☒
Overlapping contacts

 Spring return position: for a switching angle of 90° , spring return is over 30° after the last position (for a maximum of 3 simultaneous contacts).

Example:

