

# KAA1SR

operating head for cam switch - black plastic  
bezel Ø 29 mm - key - hole Ø 22 mm



## Main

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Range of product          | Harmony Series K                                  |
| Product or component type | Cam switch operating head                         |
| Component name            | KAA                                               |
| Product compatibility     | Front mounting bodies 12 and 20 A by Ø 22 mm hole |
| Cam switch head type      | With bezel Ø 29 mm, plastic with metallic finish  |
| Type of operator          | Key Ronis 455                                     |
| Rotary handle padlocking  | Without                                           |
| Presentation of legend    | With mat black legend                             |
| Switching angle           | 45 °                                              |

## Complementary

|                       |                |
|-----------------------|----------------|
| Mechanical durability | 1000000 cycles |
| CAD overall width     | 29 mm          |
| CAD overall height    | 29 mm          |
| CAD overall depth     | 69 mm          |
| Product weight        | 0.057 kg       |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Protective treatment                  | TC                                                           |
| Ambient air temperature for operation | -25...55 °C                                                  |
| Ambient air temperature for storage   | -40...70 °C                                                  |
| Shock resistance                      | 30 gn conforming to IEC 68-2-27                              |
| Vibration resistance                  | 5 gn, 10...150 Hz conforming to IEC 68-2-6                   |
| IP degree of protection               | IP65 conforming to NF C 20-010<br>IP65 conforming to IEC 529 |


The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

## Operating Head

---

For Ø 22 mm/0.87 in. Hole, Front Mounting Body



---

Operating Head

---

Panel Cut-out

