

# KBC1H48

operating head 45 x 45 mm - metallic color -  
black handle - 2 - 0 - 1



## Main

|                           |                                                   |
|---------------------------|---------------------------------------------------|
| Range of product          | Harmony Series K                                  |
| Product or component type | Cam switch operating head                         |
| Component name            | KBC                                               |
| Product compatibility     | Front mounting bodies 12 and 20 A by Ø 22 mm hole |
| Cam switch head type      | With front plate 45 x 45 mm                       |
| Type of operator          | Black handle, length = 35 mm                      |
| Rotary handle padlocking  | Without                                           |
| Presentation of legend    | With metallic legend, 2 - 0 - 1                   |
| Switching angle           | 45 °                                              |

## Complementary

|                       |                |
|-----------------------|----------------|
| Mechanical durability | 1000000 cycles |
| CAD overall width     | 45 mm          |
| CAD overall height    | 45 mm          |
| CAD overall depth     | 69 mm          |
| Length                | 35 mm          |
| Product weight        | 0.012 kg       |

## Environment

|                                       |                                                              |
|---------------------------------------|--------------------------------------------------------------|
| Protective treatment                  | TC                                                           |
| Ambient air temperature for operation | -25...55 °C                                                  |
| Ambient air temperature for storage   | -40...70 °C                                                  |
| Shock resistance                      | 30 gn conforming to IEC 68-2-27                              |
| Vibration resistance                  | 5 gn, 10...150 Hz conforming to IEC 68-2-6                   |
| IP degree of protection               | IP65 conforming to NF C 20-010<br>IP65 conforming to IEC 529 |


The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

---

## Operating Head

---

For Ø 22 mm/0.87 in. Hole, Front Mounting Body




---

Operating Head

---

Panel Cut-out



---

Marking

---

