Product datasheet Characteristics

KBC1ZR

cam switch operating head 45 x 45 mm - metallic - key - 60 °switching angle



ai

Range of product	Harmony Series K	
Product or component type	Cam switch operating head	
Component name	KBC	
Product compatibility	Front mounting bodies 12 and 20 A by Ø 22 mm hole	
Cam switch head type	<u> </u>	
	With front plate 45 x 45 mm	
Type of operator	key Ronis 455	
Rotary handle padlocking	Without	
Presentation of legend	With metallic legend	
Switching angle	60 °	
Complementary		
Mechanical durability	1000000 cycles	
CAD overall width	45 mm	
CAD overall height	45 mm	
CAD overall depth	69 mm	
Product weight	0.063 kg	
European aut		
Environment	TC	
Protective treatment	• •	
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4070 °C	
Shock resistance	30 gn conforming to IEC 68-2-27	
Vibration resistance	5 gn conforming to IEC 68-2-6 (f = 10150 Hz)	
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	
	1P03 CONIONNING TO NE C 20-010	
Offer Sustainability		
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	

Complementary

Mechanical durability	1000000 cycles
CAD overall width	45 mm
CAD overall height	45 mm
CAD overall depth	69 mm
Product weight	0.063 kg

Environment

Protective treatment	TC	
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4070 °C	
Shock resistance	30 gn conforming to IEC 68-2-27	
Vibration resistance	5 gn conforming to IEC 68-2-6 (f = 10150 Hz)	
IP degree of protection	IP65 conforming to IEC 529 IP65 conforming to NF C 20-010	

Offer Sustainability

REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Toxic heavy metal free	Yes	

Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration

Contractual warranty

Warranty	18 months