


# KG5066



## Capacitive sensor

KG-3120NFPKGP2T/US



- 1 LED ring  
2 programming buttons



### Electrical data

Operating voltage [V]	10...36 DC
Current consumption [mA]	< 20
Protection class	II
Reverse polarity protection	yes

### Outputs

Electrical design	PNP
Output function	normally open / normally closed; (selectable)
Max. voltage drop switching output DC [V]	2.5
Permanent current rating of switching output DC [mA]	200
Switching frequency DC [Hz]	10
Short-circuit proof	yes
Overload protection	yes

### Detection zone

Sensing range [mm]	12
--------------------	----

### Accuracy / deviations

Hysteresis [% of Sr]	1...15
Switch point drift [% of Sr]	-20...20

### Interfaces


Communication interface	IO-Link
Transmission type	COM1 (4,8 kBaud)
IO-Link revision	1.1
SDCI standard	IEC 61131-9 CDV
IO-Link device ID	387d / 000183h
Profiles	Smart Sensor
SIO mode	yes
Min. process cycle time [ms]	101

# KG5066



## Capacitive sensor

KG-3120NFPKGP2T/US

Operating conditions		
Ambient temperature [°C]		-25...80
Note on ambient temperature		temperature of the sensing face: -25...110 °C
Protection		IP 65; IP 67
Tests / approvals		
EMC	EN 61000-4-2 ESD	8 kV AD
	EN 61000-4-3 HF radiated	10 V/m
	EN 61000-4-4 Burst	2 kV
	EN 61000-4-6 HF conducted	3 V
	EN 55011	class B
Vibration resistance	EN 60068-2-6 Fc	(10...55 Hz) / 1 mm amplitude, oscillation period 5 min., 30 min. per axis at resonance or 55 Hz
Shock resistance	EN 60068-2-27 Ea	30 g 6 shocks / 11 ms half-sine (x, y, z)
MTTF [years]		662
Mechanical data		
Weight [g]		63.2
Housing		threaded type
Mounting		non-flush mountable
Dimensions [mm]		M18 x 1 / L = 87
Thread designation		M18 x 1
Materials		housing: PBT; plug: PC; pushbuttons: TPE-U
Displays / operating elements		
Display	switching status	1 x LED, yellow
Teach function		yes
Electronic lock		yes
Accessories		
Accessories (supplied)		lock nuts: 2
Remarks		
Pack quantity		1 pcs.
Electrical connection - plug		
Connector: 1 x M12		
		

# KG5066



## Capacitive sensor

KG-3120NFPKGP2T/US

### Connection



4: OUT / IO-Link