



### Main

Range	TeSys
Product or component type	Fuse-disconnector
Device short name	LA8D
Poles description	1P

### Complementary

Mounting support	Rail
Mounting position	Vertical (tolerance: +/- 23°)
Control type	Toggle
[Ue] rated operational voltage	600 V
[Ie] rated operational current	30 A
Local signalling	Blown fuse indication
Fuse size	10 x 38 mm
Fuse type	AM GG
Associated fuse rating	30 A aM 30 A gG
Connections - terminals	Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> solid Screw clamp terminals 2 cable(s) 1...6 mm <sup>2</sup> flexible without cable end Screw clamp terminals 2 cable(s) 1...4 mm <sup>2</sup> flexible with cable end
Tightening torque	1.7 N.m on screw clamp terminals

### Environment

Standards	IEC 60947-2 IEC 60947-1 IEC 60947-4-1
Product certifications	BV
Protective treatment	TH
Ambient air temperature for operation	-50...70 °C operation
Height	89 mm
Width	45 mm
Depth	68.3 mm

**Offer Sustainability**

REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

**Contractual warranty**

Warranty	18 months
----------	-----------