Product datasheet Characteristics

LAD4TUDL CONTACTOR BI DIRECTIONAL LIMITING DIODE



Price* : 12.87 GBP



Main

Range	TeSys	
Device short name	LAD4	
Product or component type	Suppressor module	
Product compatibility	3P LC1D09D38 4P LC1DT20DT40 4P LC1D098D258 CAD32, CAD50	9 4: 1: 2:

Complementary

Mounting location	Side
Mounting mode	By clips
Suppressor technology	Bidirectional peak limiting diode
[Uc] control circuit voltage	250 V DC
Maximum peak voltage	2 Uc
Product weight	0.012 kg

Environment

Ambient air temperature for operation	-2555 °C
Ambient air temperature for storage	-4080 °C

Offer Sustainability

LAD4T3R		Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or these products for specific user applications.
Main		ior specific
Range	TeSys	
Device short name	LAD4	0
Product or component type	Suppressor module	the second secon
Product compatibility	3P LC1D09D38 4P LC1DT20DT40 4P LC1D098D258 CAD32, CAD50	lity or reliability of
Complementary		daring suritab
Mounting location	Side	<u> </u>
Mounting mode	By clips	or det
Suppressor technology	Bidirectional peak limiting diode	
[Uc] control circuit voltage	250 V DC	
Maximum peak voltage	2 Uc	
Product weight	0.012 kg	
Environment		stifute fo
Ambient air temperature for operation	-2555 °C	
Ambient air temperature for storage	-4080 °C	
Offer Sustainability		not inte
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	len Territoria
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	er: This d
Toxic heavy metal free	Yes	Disclaim Disclaim

Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
Contractual warranty		
Warranty	18 months	