Product datasheet Characteristics

LC1DPK12P7

TeSys LC1D.K capacitor duty contactor - 3P - 33.3 kVAR - 415 V - 230 V AC coil



Price*: 193.18 GBP



Main

Range	TeSys	
Product name	TeSys LC1D.K	
Product or component type	Capacitor duty contactor	
Device short name	LC1DPK	
Contactor application	Power factor correction	
Poles description	3P	
Power pole contact composition	3 NO	
[Ue] rated operational voltage	Power circuit: <= 690 V AC 50/60 Hz	
Reactive power rating	20 kvar at 220240 V AC 50/60 Hz 55 °C 33.3 kvar at 400440 V AC 50/60 Hz 55 °C 48 kvar at 660690 V AC 50/60 Hz 55 °C	
Control circuit type	AC at 50/60 Hz	
[Uc] control circuit voltage	230 V AC 50/60 Hz	
Auxiliary contact composition	1 NO + 2 NC	
Mounting support	Rail Plate	
Standards	VDE 0560 NF C 54-100 IEC 60070 IEC 60831	
Product certifications	UL CSA	
Connections - terminals	Power circuit: connector 1 16 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 25 mm² - cable stiffness: solid with cable end Power circuit: connector 2 16 mm² - cable stiffness: solid with cable end Power circuit: connector 2 6 mm² - cable stiffness: flexible with cable end	
Tightening torque	Power circuit: 5 N.m - on connector	

Complementary

Auxiliary contacts type type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1

Environment

IP degree of protection	IP2x conforming to IEC 60529 IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068-2-30
Ambient air temperature for operation	-560 °C
Ambient air temperature for storage	-6080 °C
Operating altitude	3000 m without
Height	127 mm
Width	75 mm
Depth	150 mm
Product weight	1.3 kg

Offer Sustainability

<u> </u>		
Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Compliant EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	No need of specific recycling operations	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	

Contractual warranty

Warranty	18 months