

LC1DTK12P7

TeSys LC1D.K capacitor duty contactor - 3P - 40
kVAR - 415 V - 230 V AC coil



Price* : 290.80 GBP



Main

Range	TeSys
Product name	TeSys LC1D.K
Product or component type	Capacitor duty contactor
Device short name	LC1DTK
Contactor application	Power factor correction
Poles description	3P
Power pole contact composition	3 NO
[Ue] rated operational voltage	Power circuit: ≤ 690 V AC 50/60 Hz
Reactive power rating	25 kvar at 220...240 V AC 50/60 Hz 55 °C 40 kvar at 400...440 V AC 50/60 Hz 55 °C 58 kvar at 660...690 V AC 50/60 Hz 55 °C
Control circuit type	AC at 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
Auxiliary contact composition	1 NO + 2 NC
Mounting support	Plate Rail
Standards	IEC 60070 VDE 0560 IEC 60831 NF C 54-100
Product certifications	CSA UL
Connections - terminals	Power circuit: connector 1 16 mm² - cable stiffness: flexible with cable end Power circuit: connector 1 25 mm² - cable stiffness: solid with cable end Power circuit: connector 2 16 mm² - cable stiffness: solid with cable end Power circuit: connector 2 6 mm² - cable stiffness: flexible with cable end
Tightening torque	Power circuit: 5 N.m - on connector

Complementary

Auxiliary contacts type	type mechanically linked 1 NO + 1 NC conforming to IEC 60947-5-1
-------------------------	--

Environment

IP degree of protection	IP2x conforming to IEC 60529 IP2x conforming to VDE 0106
Protective treatment	TH conforming to IEC 60068-2-30
Ambient air temperature for operation	-5...60 °C
Ambient air temperature for storage	-60...80 °C
Operating altitude	3000 m without
Height	127 mm
Width	75 mm
Depth	150 mm
Product weight	1.3 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

Contractual warranty

Warranty	18 months
----------	-----------