





## Main

|                                             |                                                                                                                                                                                                                                                                                                                                                                                                         |
|---------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                       | TeSys                                                                                                                                                                                                                                                                                                                                                                                                   |
| Product name                                | TeSys K                                                                                                                                                                                                                                                                                                                                                                                                 |
| Device short name                           | LC1K                                                                                                                                                                                                                                                                                                                                                                                                    |
| Contactor application                       | Motor control                                                                                                                                                                                                                                                                                                                                                                                           |
| Utilisation category                        | AC-3                                                                                                                                                                                                                                                                                                                                                                                                    |
| Poles description                           | 3P                                                                                                                                                                                                                                                                                                                                                                                                      |
| Power pole contact composition              | 3 NO                                                                                                                                                                                                                                                                                                                                                                                                    |
| [Ue] rated operational voltage              | <= 690 V AC 50/60 Hz for signalling circuit<br>690 V AC 50/60 Hz for power circuit                                                                                                                                                                                                                                                                                                                      |
| [Ie] rated operational current              | 16 A at <= 440 V AC AC-3 for power circuit                                                                                                                                                                                                                                                                                                                                                              |
| Motor power kW                              | 7.5 kW at 380...415 V AC 50/60 Hz<br>4 kW at 220...230 V AC 50/60 Hz<br>5.5 kW at 440 V AC 50/60 Hz<br>4 kW at 660...690 V AC 50/60 Hz<br>4 kW at 500...600 V AC 50/60 Hz<br>4 kW at 480 V AC 50/60 Hz                                                                                                                                                                                                  |
| Control circuit type                        | AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                             |
| Control circuit voltage                     | 120 V AC 50/60 Hz                                                                                                                                                                                                                                                                                                                                                                                       |
| Auxiliary contact composition               | 1 NO                                                                                                                                                                                                                                                                                                                                                                                                    |
| [Uimp] rated impulse withstand voltage      | 8 kV                                                                                                                                                                                                                                                                                                                                                                                                    |
| Overvoltage category                        | III                                                                                                                                                                                                                                                                                                                                                                                                     |
| [Ith] conventional free air thermal current | 10 A at <= 50 °C for signalling circuit<br>20 A at <= 50 °C for power circuit                                                                                                                                                                                                                                                                                                                           |
| Irms rated making capacity                  | 160 A AC for power circuit conforming to IEC 60947<br>160 A AC for power circuit conforming to NF C 63-110<br>110 A AC for signalling circuit conforming to IEC 60947                                                                                                                                                                                                                                   |
| Rated breaking capacity                     | 70 A at 660...690 V conforming to IEC 60947<br>80 A at 500 V conforming to IEC 60947<br>110 A at 440 V conforming to IEC 60947                                                                                                                                                                                                                                                                          |
| [Icw] rated short-time withstand current    | 25 A <= 50 °C >= 15 s power circuit<br>50 A <= 50 °C 3 min power circuit<br>55 A <= 50 °C 1 min power circuit<br>75 A <= 50 °C 30 s power circuit<br>100 A <= 50 °C 10 s power circuit<br>105 A <= 50 °C 5 s power circuit<br>115 A <= 50 °C 1 s power circuit<br>110 A 100 ms signalling circuit<br>90 A 500 ms signalling circuit<br>80 A 1 s signalling circuit                                      |
| Associated fuse rating                      | 10 A gG for signalling circuit conforming to VDE 0660<br>10 A gG for signalling circuit conforming to IEC 60947<br>25 A aM for power circuit<br>25 A gG at <= 440 V for power circuit                                                                                                                                                                                                                   |
| Average impedance                           | 3 mOhm at 50 Hz - Ith 20 A for power circuit                                                                                                                                                                                                                                                                                                                                                            |
| [Ui] rated insulation voltage               | 600 V for signalling circuit conforming to CSA C22.2 No 14<br>600 V for power circuit conforming to CSA C22.2 No 14<br>600 V for signalling circuit conforming to UL 508<br>690 V for signalling circuit conforming to IEC 60947-5-1<br>690 V for signalling circuit conforming to IEC 60947-4-1<br>690 V for power circuit conforming to IEC 60947-4-1<br>600 V for power circuit conforming to UL 508 |
| Electrical durability                       | 1.3 Mcycles 16 A AC-3 at Ue <= 440 V                                                                                                                                                                                                                                                                                                                                                                    |
| Mounting support                            | Plate<br>Rail                                                                                                                                                                                                                                                                                                                                                                                           |

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standards                | BS 5424<br>IEC 60947<br>NF C 63-110<br>VDE 0660                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Product certifications   | CSA<br>UL                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Connections - terminals  | Screw clamp terminals 2 cable(s) 0.34...1.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Screw clamp terminals 2 cable(s) 0.75...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 2 cable(s) 1.5...4 mm <sup>2</sup> - cable stiffness: solid<br>Screw clamp terminals 1 cable(s) 0.34...2.5 mm <sup>2</sup> - cable stiffness: flexible - with cable end<br>Screw clamp terminals 1 cable(s) 0.75...4 mm <sup>2</sup> - cable stiffness: flexible - without cable end<br>Screw clamp terminals 1 cable(s) 1.5...4 mm <sup>2</sup> - cable stiffness: solid |
| Tightening torque        | 1.3 N.m - on screw clamp terminals - with screwdriver flat Ø 6 mm<br>1.3 N.m - on screw clamp terminals - with screwdriver Philips No 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
| Operating time           | 10...20 ms coil energisation and NO closing<br>10...20 ms coil de-energisation and NO opening                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| Safety reliability level | B10d = 2000000 cycles contactor with mechanical load conforming to EN/ISO 13849-1<br>B10d = 1369863 cycles contactor with nominal load conforming to EN/ISO 13849-1                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| Mechanical durability    | 10 Mcycles                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| Operating rate           | 3600 cyc/h                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## Complementary

|                                 |                                                                           |
|---------------------------------|---------------------------------------------------------------------------|
| Control circuit voltage limits  | 0.2...0.75 Uc at ≤ 50 °C drop-out<br>0.8...1.15 Uc at ≤ 50 °C operational |
| Inrush power in VA              | 30 VA at 20 °C                                                            |
| Hold-in power consumption in VA | 4.5 VA at 20 °C                                                           |
| Heat dissipation                | 1.3 W                                                                     |
| Auxiliary contacts type         | Type instantaneous (1 NO)                                                 |
| Signalling circuit frequency    | ≤ 400 Hz                                                                  |
| Minimum switching current       | 5 mA for signalling circuit                                               |
| Minimum switching voltage       | 17 V for signalling circuit                                               |
| Non overlap distance            | 0.5 mm                                                                    |
| Insulation resistance           | > 10 MOhm for signalling circuit                                          |

## Environment

|                                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|-------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| IP degree of protection             | IP2x conforming to VDE 0106                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Protective treatment                | TC conforming to DIN 50016<br>TC conforming to IEC 60068                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| Ambient air temperature for storage | -50...80 °C                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| Operating altitude                  | 2000 m without derating in temperature                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| Flame retardance                    | Requirement 2 conforming to NF F 16-102<br>Requirement 2 conforming to NF F 16-101<br>V1 conforming to UL 94                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Mechanical robustness               | Vibrations contactor opened 2 Gn, 5...300 Hz IEC 60068-2-6<br>Vibrations contactor closed 4 Gn, 5...300 Hz IEC 60068-2-6<br>Shocks contactor opened, on Z axis 10 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor opened, on Y axis 10 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor opened, on X axis 6 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor closed, on Z axis 15 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor closed, on Y axis 15 Gn for 11 ms IEC 60068-2-27<br>Shocks contactor closed, on X axis 10 Gn for 11 ms IEC 60068-2-27 |
| Depth                               | 57 mm                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Product weight                      | 0.18 kg                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS                             | Compliant - since 0825 - <a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |