

# LC4D32AM7

on mounting plate DOL starter - TeSys LC4-D -  
32 A - coil 220 V AC



## Main

|                                |                                                                                                                                                                                                         |
|--------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product               | TeSys                                                                                                                                                                                                   |
| Device short name              | LC4                                                                                                                                                                                                     |
| Product or component type      | DOL starter                                                                                                                                                                                             |
| Motor power kW                 | 15 kW at 380...400 V AC 50/60 Hz<br>15 kW at 415 V AC 50/60 Hz<br>15 kW at 440 V AC 50/60 Hz<br>7.5 kW at 220...230 V AC 50/60 Hz<br>18.5 kW at 500 V AC 50/60 Hz<br>18.5 kW at 660...690 V AC 50/60 Hz |
| Utilisation category           | AC-3                                                                                                                                                                                                    |
| [Ue] rated operational voltage | 220 V AC 50/60 Hz                                                                                                                                                                                       |
| [Ie] rated operational current | 32 A                                                                                                                                                                                                    |

## Complementary

|                    |                                 |
|--------------------|---------------------------------|
| Device composition | Contacteur<br>Fuse disconnecter |
| Mounting support   | Plate                           |
| Width              | 164 mm                          |
| Height             | 124 mm                          |
| Depth              | 98 mm                           |
| Product weight     | 2.63 kg                         |

## Offer Sustainability

|                          |                                                  |
|--------------------------|--------------------------------------------------|
| Sustainable offer status | Green Premium product                            |
| REACH Regulation         | <a href="#">REACH Declaration</a>                |
| REACH free of SVHC       | Yes                                              |
| EU RoHS Directive        | Compliant<br><a href="#">EU RoHS Declaration</a> |
| Toxic heavy metal free   | Yes                                              |

|                            |                                                                                                                             |
|----------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Mercury free               | Yes                                                                                                                         |
| RoHS exemption information | <a href="#">Yes</a>                                                                                                         |
| China RoHS Regulation      | <a href="#">China RoHS declaration</a>                                                                                      |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>                                                                               |
| Circularity Profile        | <a href="#">End of Life Information</a>                                                                                     |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins |

### Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|