

Main

Range of product	TeSys
Product name	LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay to be ordered separately Contactor
[Ie] rated operational current	12 A AC-3
Motor power kW	5.5 kW at 440 V AC 50/60 Hz 5.5 kW at 415 V AC 50/60 Hz 5.5 kW at 380/400 V AC 50/60 Hz 7.5 kW at 660/690 V AC 50/60 Hz 7.5 kW at 500 V AC 50/60 Hz 3 kW at 220/230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	12 A
[Uc] control circuit voltage	42 V AC 50/60 Hz
Control type	Selector switch 3 positions automatic start/stop/ manual start I-O-II Pushbutton reset blue R

Complementary

Cable entry number	2 cable entry :Pg 16 bottom 2 cable entry :Pg 13 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO20 top
Width	88 mm
Height	166 mm
Depth	135 mm
Product weight	0.92 kg

Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C