

Main

Range of product	TeSys
Product name	LE
Device short name	LE1D
Product or component type	Enclosed DOL starter
Device application	Standard
Utilisation category	AC-3
Device composition	Neutral terminal Thermal overload relay to be ordered separately Contactor
[Ie] rated operational current	18 A AC-3
Motor power kW	7.5 kW at 380/400 V AC 50/60 Hz 9 kW at 440 V AC 50/60 Hz 9 kW at 415 V AC 50/60 Hz 4 kW at 220/230 V AC 50/60 Hz 10 kW at 660/690 V AC 50/60 Hz 10 kW at 500 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	18 A
[Uc] control circuit voltage	115 V AC 50/60 Hz
Control type	Pushbutton stop/reset red O Pushbutton start green I

Complementary

Cable entry number	2 cable entry :ISO25 bottom 2 cable entry :Pg 21 bottom 2 cable entry :ISO25 top 2 cable entry :Pg 16 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO20 top
Width	101 mm
Height	201 mm
Depth	153.5 mm
Product weight	1.015 kg

Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C