



### Main

|                                              |                                                                                                                                                                                               |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                        | TeSys                                                                                                                                                                                         |
| Product name                                 | TeSys LE                                                                                                                                                                                      |
| Device short name                            | LE1D                                                                                                                                                                                          |
| Product or component type                    | Enclosed DOL starter                                                                                                                                                                          |
| Device application                           | Standard                                                                                                                                                                                      |
| Utilisation category                         | AC-3                                                                                                                                                                                          |
| Device composition                           | Contacteur<br>Thermal overload relay to be ordered separately                                                                                                                                 |
| [Ie] rated operational current               | 25 A AC-3                                                                                                                                                                                     |
| Motor power kW                               | 5.5 kW at 220/230 V AC 50/60 Hz<br>15 kW at 660/690 V AC 50/60 Hz<br>15 kW at 500 V AC 50/60 Hz<br>11 kW at 440 V AC 50/60 Hz<br>11 kW at 415 V AC 50/60 Hz<br>11 kW at 380/400 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 25 A                                                                                                                                                                                          |
| [Uc] control circuit voltage                 | 115 V AC 50/60 Hz                                                                                                                                                                             |
| Control type                                 | Push-button stop/reset red O<br>Push-button start green I                                                                                                                                     |

### Complementary

|                    |                                                                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 2 cable entry :ISO25 bottom<br>2 cable entry :Pg 21 bottom<br>2 cable entry :ISO25 top<br>2 cable entry :Pg 16 bottom<br>2 cable entry :ISO20 bottom<br>2 cable entry :ISO20 top |
| Width              | 101 mm                                                                                                                                                                           |
| Height             | 201 mm                                                                                                                                                                           |
| Depth              | 153.5 mm                                                                                                                                                                         |
| Product weight     | 1.015 kg                                                                                                                                                                         |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Material                              | Polycarbonate                |
| IP degree of protection               | IP65 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |

### Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS                             | Compliant - since 0817 - <a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |