

# LE1D25N7A35

TeSys LE - enclosed DOL starter - 25 A - 415 V AC coil - selector 3 pos + reset

## Main

|                                              |                                                                                                                                                                                               |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                             | TeSys                                                                                                                                                                                         |
| Product name                                 | LE                                                                                                                                                                                            |
| Device short name                            | LE1D                                                                                                                                                                                          |
| Product or component type                    | Enclosed DOL starter                                                                                                                                                                          |
| Device application                           | Standard                                                                                                                                                                                      |
| Utilisation category                         | AC-3                                                                                                                                                                                          |
| Device composition                           | Thermal overload relay to be ordered separately<br>Contactor                                                                                                                                  |
| [Ie] rated operational current               | 25 A AC-3                                                                                                                                                                                     |
| Motor power kW                               | 5.5 kW at 220/230 V AC 50/60 Hz<br>15 kW at 660/690 V AC 50/60 Hz<br>15 kW at 500 V AC 50/60 Hz<br>11 kW at 440 V AC 50/60 Hz<br>11 kW at 415 V AC 50/60 Hz<br>11 kW at 380/400 V AC 50/60 Hz |
| [Ithe] conventional enclosed thermal current | 25 A                                                                                                                                                                                          |
| [Uc] control circuit voltage                 | 415 V AC 50/60 Hz                                                                                                                                                                             |
| Control type                                 | Selector switch 3 positions start spring return/stop<br>O-I<br>Pushbutton reset blue R                                                                                                        |

## Complementary

|                    |                                                                                                                                                                                  |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 2 cable entry :ISO25 bottom<br>2 cable entry :Pg 21 bottom<br>2 cable entry :ISO25 top<br>2 cable entry :Pg 16 bottom<br>2 cable entry :ISO20 bottom<br>2 cable entry :ISO20 top |
| Width              | 101 mm                                                                                                                                                                           |
| Height             | 201 mm                                                                                                                                                                           |
| Depth              | 160 mm                                                                                                                                                                           |
| Product weight     | 1.015 kg                                                                                                                                                                         |

## Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| Material                              | Polycarbonate                |
| IP degree of protection               | IP65 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.