

Main

Range of product	TeSys
Product name	LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay to be ordered separately Reversing contactor
[Ie] rated operational current	40 A AC-3
Motor power kW	18.5 kW at 380/400 V AC 50/60 Hz 30 kW at 660/690 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 11 kW at 220/230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	40 A
[Uc] control circuit voltage	220 V AC 50/60 Hz
Control type	Pushbutton reset blue R

Complementary

Cable entry number	2 cable entry :1 Pg 13 + 1 Pg 21 top 3 cable entry :1 ISO20 + 2 ISO25 bottom 3 cable entry :1 Pg 13 + 2 Pg 21 bottom 2 cable entry :1 ISO20 + 1 ISO25 top
Width	257 mm
Height	307 mm
Depth	176 mm
Product weight	5.27 kg

Environment

Material	Sheet steel
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C