



Main

Range of product	TeSys
Product name	LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnect Thermal overload relay ordered separately Reversing contactor
[Ie] rated operational current	40 A AC-3
Motor power kW	18.5 kW at 380/400 V AC 50/60 Hz 30 kW at 660/690 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 11 kW at 220/230 V AC 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	40 A
Associated fuse rating	40 A 14 x 51 mm aM
Control type	Without

Complementary

Cable entry number	2 cable entry :1 Pg 13 + 1 Pg 21 top 3 cable entry :1 ISO20 + 2 ISO25 bottom 3 cable entry :1 Pg 13 + 2 Pg 21 bottom 2 cable entry :1 ISO20 + 1 ISO25 top
Width	300 mm
Height	325 mm
Depth	218 mm
Product weight	14.17 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C