

LE2D65AFE7A04

TeSys LE - enclosed DOL reversing starter - 65 A - 115 V AC coil - no pushbutton



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Device composition	Reversing contactor Thermal overload relay to be ordered separately
[Ie] rated operational current	65 A AC-3
Motor power kW	18.5 kW at 220/230 V AC 50/60 Hz 37 kW at 660/690 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz 37 kW at 440 V AC 50/60 Hz 37 kW at 415 V AC 50/60 Hz 30 kW at 380/400 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	65 A
[Uc] control circuit voltage	115 V AC 50/60 Hz
Control type	Without

Complementary

Cable entry number	3 cable entry :1 ISO20 + 2 ISO32 bottom 1 cable entry :ISO32 top
Width	200 mm
Height	300 mm
Depth	150 mm
Product weight	5.47 kg

Environment

Material	Sheet steel
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.