



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE2D
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Device composition	Reversing contactor Thermal overload relay to be ordered separately
[Ie] rated operational current	65 A AC-3
Motor power kW	18.5 kW at 220/230 V AC 50/60 Hz 37 kW at 660/690 V AC 50/60 Hz 37 kW at 500 V AC 50/60 Hz 37 kW at 440 V AC 50/60 Hz 37 kW at 415 V AC 50/60 Hz 30 kW at 380/400 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	65 A
[Uc] control circuit voltage	380 V AC 50/60 Hz
Control type	Selector switch 2 positions start I-II Push-button stop/reset red O

Complementary

Cable entry number	3 cable entry :1 ISO20 + 2 ISO32 bottom 1 cable entry :ISO32 top
Width	200 mm
Height	300 mm
Depth	174 mm
Product weight	5.47 kg

Environment

Material	Sheet steel
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C