



Main

Range of product	TeSys
Product name	LE
Device short name	LE2K
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Device composition	Thermal overload relay to be ordered separately Reversing contactor
[Ie] rated operational current	6 A AC-3
Motor power kW	2.2 kW at 415 V AC 50/60 Hz 2.2 kW at 380/400 V AC 50/60 Hz 1.5 kW at 220/230 V AC 50/60 Hz 3 kW at 440 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	6 A
[Uc] control circuit voltage	110 V AC 50/60 Hz
Control type	Pushbutton start up arrow Pushbutton start down arrow Pushbutton stop/reset red O

Complementary

Cable entry number	4 cable entry :ISO20 bottom 4 cable entry :2 Pg 13 + 2 Pg 16 bottom 4 cable entry :ISO20 top 4 cable entry :2 Pg 13 + 2 Pg 16 top
Width	175 mm
Height	165 mm
Depth	146 mm
Product weight	1.08 kg

Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0832 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations