



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE2K
Product or component type	Enclosed DOL reversing starter
Device application	Standard
Utilisation category	AC-3
Device composition	Reversing contactor Thermal overload relay to be ordered separately
[Ie] rated operational current	6 A AC-3
Motor power kW	2.2 kW at 415 V AC 50/60 Hz 2.2 kW at 380/400 V AC 50/60 Hz 1.5 kW at 220/230 V AC 50/60 Hz 3 kW at 440 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	6 A
[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Push-button start up arrow Push-button start down arrow Push-button stop/reset red O

Complementary

Cable entry number	4 cable entry :ISO20 bottom 4 cable entry :2 Pg 13 + 2 Pg 16 bottom 4 cable entry :ISO20 top 4 cable entry :2 Pg 13 + 2 Pg 16 top
Width	175 mm
Height	165 mm
Depth	146 mm
Product weight	1.08 kg

Environment

Material	Polycarbonate
IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0832 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations