



Main

Range of product	TeSys
Product name	LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Mechanical interlock Thermal overload relay ordered separately Star-delta contactors
Motor power kW	5.5 kW at 220 V AC 50/60 Hz 11 kW at 440 V AC 50/60 Hz 11 kW at 415 V AC 50/60 Hz 11 kW at 380/400 V AC 50/60 Hz
[Uc] control circuit voltage	220 V AC 50/60 Hz
Control type	Pushbutton stop/reset red O Pushbutton start green I

Complementary

Cable entry number	2 cable entry :ISO40 bottom 2 cable entry :ISO32 bottom 2 cable entry :ISO25 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO40 top 2 cable entry :ISO32 top 2 cable entry :ISO25 top 2 cable entry :ISO20 top
Width	186 mm
Height	348 mm
Depth	175.5 mm
Product weight	3.65 kg

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0844 - Schneider Electric declaration of conformity