

### Main

Range of product	TeSys
Product name	LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnecter Thermal overload relay ordered separately Star-delta contactors
Motor power kW	30 kW at 440 V AC 50/60 Hz 30 kW at 415 V AC 50/60 Hz 30 kW at 380/400 V AC 50/60 Hz 15 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	115 V AC 50/60 Hz
Associated fuse rating	63 A 14 x 51 mm aM
Control type	Pushbutton reset blue R

### Complementary

Cable entry number	5 cable entry :1 ISO32 + 2 ISO20 + 2 ISO25 bottom 5 cable entry :1 Pg 21 + 2 Pg 13 + 2 Pg 16 bottom 1 cable entry :ISO32 top 1 cable entry :Pg 21 top
Width	287 mm
Height	367 mm
Depth	190 mm
Product weight	7.65 kg

### Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C