



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Mechanical interlock Star-delta contactors Thermal overload relay ordered separately
Motor power kW	30 kW at 440 V AC 50/60 Hz 30 kW at 415 V AC 50/60 Hz 30 kW at 380/400 V AC 50/60 Hz 15 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	400 V AC 50/60 Hz
Control type	Without

Complementary

Cable entry number	2 cable entry :ISO40 bottom 2 cable entry :ISO32 bottom 2 cable entry :ISO25 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO40 top 2 cable entry :ISO32 top 2 cable entry :ISO25 top 2 cable entry :ISO20 top
Width	186 mm
Height	348 mm
Depth	167 mm
Product weight	5.16 kg

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0851 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations