

### Main

|                              |                                                                                                                            |
|------------------------------|----------------------------------------------------------------------------------------------------------------------------|
| Range of product             | TeSys                                                                                                                      |
| Product name                 | LE                                                                                                                         |
| Device short name            | LE3D                                                                                                                       |
| Product or component type    | Enclosed star-delta starter                                                                                                |
| Device application           | Standard                                                                                                                   |
| Material                     | Sheet steel                                                                                                                |
| Utilisation category         | AC-3                                                                                                                       |
| Device composition           | Thermal overload relay ordered separately<br>Star-delta contactors                                                         |
| Motor power kW               | 18.5 kW at 220 V AC 50/60 Hz<br>37 kW at 440 V AC 50/60 Hz<br>37 kW at 415 V AC 50/60 Hz<br>37 kW at 380/400 V AC 50/60 Hz |
| [Uc] control circuit voltage | 24 V AC 50/60 Hz                                                                                                           |
| Control type                 | Without                                                                                                                    |

### Complementary

|                    |                                                                                                                                                                |
|--------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 5 cable entry :1 ISO32 + 2 ISO20 + 2 ISO25 bottom<br>5 cable entry :1 Pg 29 + 2 Pg 13 + 2 Pg 21 bottom<br>1 cable entry :ISO32 top<br>1 cable entry :Pg 29 top |
| Width              | 367 mm                                                                                                                                                         |
| Height             | 287 mm                                                                                                                                                         |
| Depth              | 190 mm                                                                                                                                                         |
| Product weight     | 8.16 kg                                                                                                                                                        |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| IP degree of protection               | IP55 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.