

Main

Range of product	TeSys
Product name	LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Mechanical interlock Thermal overload relay ordered separately Star-delta contactors
Motor power kW	18.5 kW at 220 V AC 50/60 Hz 37 kW at 440 V AC 50/60 Hz 37 kW at 415 V AC 50/60 Hz 37 kW at 380/400 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
Control type	Without

Complementary

Cable entry number	5 cable entry :1 ISO32 + 2 ISO20 + 2 ISO25 bottom 5 cable entry :1 Pg 29 + 2 Pg 13 + 2 Pg 21 bottom 1 cable entry :ISO32 top 1 cable entry :Pg 29 top
Width	367 mm
Height	287 mm
Depth	190 mm
Product weight	8.16 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the Schneider Electric group. It is not intended to be used as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.