



Main

Range of product	TeSys
Product name	LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnecter Thermal overload relay ordered separately Star-delta contactors
Motor power kW	37 kW at 440 V AC 50/60 Hz 37 kW at 415 V AC 50/60 Hz 37 kW at 380/400 V AC 50/60 Hz 18.5 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
Associated fuse rating	80 A 14 x 51 mm aM
Control type	Pushbutton stop/reset red O Pushbutton start green I

Complementary

Cable entry number	5 cable entry :1 Pg 29 + 2 Pg 13 + 2 Pg 21 bottom 1 cable entry :Pg 29 top 5 cable entry :1 ISO32 + 2 ISO20 + 2 ISO25 bottom 1 cable entry :ISO32 top
Width	400 mm
Height	500 mm
Depth	218 mm
Product weight	16.9 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C