

Main

Range of product	TeSys
Product name	LE
Device short name	LE3D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Thermal overload relay ordered separately Star-delta contactors
Motor power kW	75 kW at 440 V AC 50/60 Hz 75 kW at 415 V AC 50/60 Hz 75 kW at 380/400 V AC 50/60 Hz 37 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	115 V AC 50/60 Hz
Control type	Pushbutton stop/reset red O Pushbutton start green I

Complementary

Cable entry number	5 cable entry :2 ISO20 + 3 ISO40 bottom 5 cable entry :2 Pg 13 + 3 Pg 36 bottom 1 cable entry :ISO40 top 1 cable entry :Pg 36 top
Width	400 mm
Height	400 mm
Depth	218 mm
Product weight	14 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.