



Main

Range of product	TeSys
Product name	LE
Device short name	LE3F
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Thermal overload relay ordered separately Star-delta contactors
Motor power kW	90 kW at 220 V AC 50/60 Hz 185 kW at 440 V AC 50/60 Hz 160 kW at 415 V AC 50/60 Hz 160 kW at 380 V AC 50/60 Hz
[Uc] control circuit voltage	400 V AC 50/60 Hz
Control type	Without

Complementary

Cable entry number	6 cable entry :2 Pg 13 + 4 Pg 48 bottom 2 cable entry :Pg 48 top
Width	600 mm
Height	700 mm
Depth	319 mm
Product weight	31.4 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.