



### Main

|                              |                                                                                                                          |
|------------------------------|--------------------------------------------------------------------------------------------------------------------------|
| Range of product             | TeSys                                                                                                                    |
| Product name                 | LE                                                                                                                       |
| Device short name            | LE3F                                                                                                                     |
| Product or component type    | Enclosed star-delta starter                                                                                              |
| Device application           | Standard                                                                                                                 |
| Material                     | Sheet steel                                                                                                              |
| Utilisation category         | AC-3                                                                                                                     |
| Device composition           | Thermal overload relay ordered separately<br>Star-delta contactors                                                       |
| Motor power kW               | 375 kW at 440 V AC 50/60 Hz<br>355 kW at 415 V AC 50/60 Hz<br>315 kW at 380 V AC 50/60 Hz<br>185 kW at 220 V AC 50/60 Hz |
| [Uc] control circuit voltage | 400 V AC 50/60 Hz                                                                                                        |
| Control type                 | Without                                                                                                                  |

### Complementary

|                |         |
|----------------|---------|
| Width          | 800 mm  |
| Height         | 1000 mm |
| Depth          | 419 mm  |
| Product weight | 82 kg   |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| IP degree of protection               | IP55 conforming to IEC 60529 |
| IK degree of protection               | IK09 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |