



Main

Range	TeSys
Product name	TeSys LE
Device short name	LE4D
Product or component type	Enclosed DOL starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Fuse disconnecter Contactor Thermal overload relay ordered separately
[Ie] rated operational current	9 A AC-3
Motor power kW	5.5 kW at 500 V AC 50/60 Hz 2.2 kW at 220/230 V AC 50/60 Hz 4 kW at 440 V AC 50/60 Hz 4 kW at 415 V AC 50/60 Hz 4 kW at 380/400 V AC 50/60 Hz
[Uc] control circuit voltage	440 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	9 A
Associated fuse rating	12 A 10 x 38 mm aM
Control type	Push-button stop/reset red O Push-button start green I

Complementary

Cable entry number	2 cable entry :ISO40 bottom 2 cable entry :ISO32 bottom 2 cable entry :ISO25 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO40 top 2 cable entry :ISO32 top 2 cable entry :ISO25 top 2 cable entry :ISO20 top
Width	186 mm
Height	330 mm
Depth	175.5 mm
Product weight	1.96 kg

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0925 - Schneider Electric declaration of conformity
Product environmental profile	Available Download Product Environmental
Product end of life instructions	Need no specific recycling operations