

Main

Range of product	TeSys
Product name	LE
Device short name	LE4D
Product or component type	Enclosed DOL starter
Device application	Standard
Material	Sheet steel
Utilisation category	AC-3
Device composition	Fuse disconnecter Thermal overload relay ordered separately Contactor
[Ie] rated operational current	40 A AC-3
Motor power kW	18.5 kW at 380/400 V AC 50/60 Hz 30 kW at 660/690 V AC 50/60 Hz 22 kW at 500 V AC 50/60 Hz 22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 11 kW at 220/230 V AC 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	40 A
Associated fuse rating	40 A 14 x 51 mm aM
Control type	Without

Complementary

Cable entry number	3 cable entry :1 ISO20 + 2 ISO25 bottom 3 cable entry :1 Pg 13 + 2 Pg 21 bottom 2 cable entry :1 ISO20 + 1 ISO25 top 2 cable entry :1 Pg 13 + 1 Pg 21 top
Width	367 mm
Height	195 mm
Depth	190 mm
Product weight	5.77 kg

Environment

IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C