

### Main

|                                              |                                                                                                                                                                                                |
|----------------------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range of product                             | TeSys                                                                                                                                                                                          |
| Product name                                 | LE                                                                                                                                                                                             |
| Device short name                            | LE4D                                                                                                                                                                                           |
| Product or component type                    | Enclosed DOL starter                                                                                                                                                                           |
| Device application                           | Standard                                                                                                                                                                                       |
| Material                                     | Sheet steel                                                                                                                                                                                    |
| Utilisation category                         | AC-3                                                                                                                                                                                           |
| Device composition                           | Fuse disconnecter<br>Thermal overload relay ordered separately<br>Contactor                                                                                                                    |
| [Ie] rated operational current               | 40 A AC-3                                                                                                                                                                                      |
| Motor power kW                               | 18.5 kW at 380/400 V AC 50/60 Hz<br>30 kW at 660/690 V AC 50/60 Hz<br>22 kW at 500 V AC 50/60 Hz<br>22 kW at 440 V AC 50/60 Hz<br>22 kW at 415 V AC 50/60 Hz<br>11 kW at 220/230 V AC 50/60 Hz |
| [Uc] control circuit voltage                 | 230 V AC 50/60 Hz                                                                                                                                                                              |
| [Ithe] conventional enclosed thermal current | 40 A                                                                                                                                                                                           |
| Associated fuse rating                       | 40 A 14 x 51 mm aM                                                                                                                                                                             |
| Control type                                 | Pushbutton reset blue R                                                                                                                                                                        |

### Complementary

|                    |                                                                                                                                                                    |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 3 cable entry :1 ISO20 + 2 ISO25 bottom<br>3 cable entry :1 Pg 13 + 2 Pg 21 bottom<br>2 cable entry :1 ISO20 + 1 ISO25 top<br>2 cable entry :1 Pg 13 + 1 Pg 21 top |
| Width              | 367 mm                                                                                                                                                             |
| Height             | 195 mm                                                                                                                                                             |
| Depth              | 201 mm                                                                                                                                                             |
| Product weight     | 5.77 kg                                                                                                                                                            |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| IP degree of protection               | IP55 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |