



Main

Range of product	TeSys
Product name	LE
Device short name	LE4K
Product or component type	Enclosed DOL starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Neutral terminal Fuse disconnecter Thermal overload relay ordered separately Contactor
[Ie] rated operational current	6 A AC-3
Motor power kW	2.2 kW at 415 V AC 50/60 Hz 2.2 kW at 380/400 V AC 50/60 Hz 1.5 kW at 220/230 V AC 50/60 Hz 3 kW at 440 V AC 50/60 Hz
[Uc] control circuit voltage	230 V AC 50/60 Hz
[Ithe] conventional enclosed thermal current	6 A
Associated fuse rating	10 A 10 x 38 mm aM
Control type	Pushbutton stop/reset red O Pushbutton start green I

Complementary

Cable entry number	4 cable entry :2 Pg 13 + 2 Pg 16 bottom 4 cable entry :ISO20 bottom 4 cable entry :2 Pg 13 + 2 Pg 16 top 4 cable entry :ISO20 top
Width	175 mm
Height	165 mm
Depth	146 mm
Product weight	1.45 kg

Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK09 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C