



### Main

Range	TeSys
Product name	TeSys LE
Device short name	LE6D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Mechanical interlock Fuse disconnecter Star-delta contactors Thermal overload relay ordered separately
Motor power kW	22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 18.5 kW at 380/400 V AC 50/60 Hz 11 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	24 V AC 50/60 Hz
Associated fuse rating	40 A 14 x 51 mm aM
Control type	Push-button stop/reset red O Push-button start green I

### Complementary

Cable entry number	2 cable entry :ISO40 bottom 2 cable entry :ISO32 bottom 2 cable entry :ISO25 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO40 top 2 cable entry :ISO32 top 2 cable entry :ISO25 top 2 cable entry :ISO20 top
Width	186 mm
Height	348 mm
Depth	175.5 mm
Product weight	4.85 kg

### Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS	Compliant - since 0925 - <a href="#">Schneider Electric declaration of conformity</a>
Product environmental profile	Available <a href="#">Download Product Environmental</a>
Product end of life instructions	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.