

### Main

Range of product	TeSys
Product name	LE
Device short name	LE6D
Product or component type	Enclosed star-delta starter
Device application	Standard
Material	Polycarbonate
Utilisation category	AC-3
Device composition	Neutral terminal Mechanical interlock Fuse disconnecter Thermal overload relay ordered separately Star-delta contactors
[Ie] rated operational current	18 A AC-3
Motor power kW	22 kW at 440 V AC 50/60 Hz 22 kW at 415 V AC 50/60 Hz 18.5 kW at 380/400 V AC 50/60 Hz 11 kW at 220 V AC 50/60 Hz
[Uc] control circuit voltage	400 V AC 50/60 Hz
Associated fuse rating	40 A 14 x 51 mm aM
Control type	Pushbutton stop/reset red O Pushbutton start green I

### Complementary

Cable entry number	2 cable entry :ISO40 bottom 2 cable entry :ISO32 bottom 2 cable entry :ISO25 bottom 2 cable entry :ISO20 bottom 2 cable entry :ISO40 top 2 cable entry :ISO32 top 2 cable entry :ISO25 top 2 cable entry :ISO20 top
Width	186 mm
Height	348 mm
Depth	175.5 mm
Product weight	4.85 kg

### Environment

IP degree of protection	IP65 conforming to IEC 60529
IK degree of protection	IK07 conforming to IEC 60529
Standards	IEC 60947-4-1
Ambient air temperature for operation	-5...40 °C