



### Main

|                                              |                                                                                                                                                          |
|----------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
| Range                                        | TeSys                                                                                                                                                    |
| Product name                                 | TeSys LE                                                                                                                                                 |
| Device short name                            | LE8D                                                                                                                                                     |
| Product or component type                    | Enclosed DOL reversing starter                                                                                                                           |
| Device application                           | Standard                                                                                                                                                 |
| Material                                     | Polycarbonate                                                                                                                                            |
| Utilisation category                         | AC-3                                                                                                                                                     |
| Device composition                           | Fuse disconnecter<br>Reversing contactor<br>Thermal overload relay ordered separately                                                                    |
| [Ie] rated operational current               | 18 A AC-3                                                                                                                                                |
| Motor power kW                               | 7.5 kW at 380/400 V AC 50/60 Hz<br>9 kW at 440 V AC 50/60 Hz<br>9 kW at 415 V AC 50/60 Hz<br>4 kW at 220/230 V AC 50/60 Hz<br>10 kW at 500 V AC 50/60 Hz |
| [Uc] control circuit voltage                 | 400 V AC 50/60 Hz                                                                                                                                        |
| [Ithe] conventional enclosed thermal current | 18 A                                                                                                                                                     |
| Associated fuse rating                       | 20 A 10 x 38 mm aM                                                                                                                                       |
| Control type                                 | Selector switch 2 positions start I-II<br>Push-button stop/reset red O                                                                                   |

### Complementary

|                    |                                                                                                                                                                                                                                          |
|--------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Cable entry number | 2 cable entry :ISO40 bottom<br>2 cable entry :ISO32 bottom<br>2 cable entry :ISO25 bottom<br>2 cable entry :ISO20 bottom<br>2 cable entry :ISO40 top<br>2 cable entry :ISO32 top<br>2 cable entry :ISO25 top<br>2 cable entry :ISO20 top |
| Width              | 186 mm                                                                                                                                                                                                                                   |
| Height             | 348 mm                                                                                                                                                                                                                                   |
| Depth              | 182 mm                                                                                                                                                                                                                                   |
| Product weight     | 3.7 kg                                                                                                                                                                                                                                   |

### Environment

|                                       |                              |
|---------------------------------------|------------------------------|
| IP degree of protection               | IP65 conforming to IEC 60529 |
| IK degree of protection               | IK07 conforming to IEC 60529 |
| Standards                             | IEC 60947-4-1                |
| Ambient air temperature for operation | -5...40 °C                   |

## Offer Sustainability

|                                  |                                                                                       |
|----------------------------------|---------------------------------------------------------------------------------------|
| Sustainable offer status         | Green Premium product                                                                 |
| RoHS                             | Compliant - since 0925 - <a href="#">Schneider Electric declaration of conformity</a> |
| Product environmental profile    | Available <a href="#">Download Product Environmental</a>                              |
| Product end of life instructions | Need no specific recycling operations                                                 |