

# LG8K06P708A39

TeSys LG - enclosed DOL reversing starter -  
2.5...4 A - 230 V AC coil no emerg



## Main

|                                     |                                                                                                    |
|-------------------------------------|----------------------------------------------------------------------------------------------------|
| Range of product                    | TeSys                                                                                              |
| Product name                        | LG                                                                                                 |
| Device short name                   | LG8K                                                                                               |
| Product or component type           | Enclosed DOL reversing starter                                                                     |
| Device application                  | Safety                                                                                             |
| Utilisation category                | AC-3                                                                                               |
| Device composition                  | Circuit-breaker<br>Reversing contactor                                                             |
| Motor power kW                      | 1.5 kW at 440 V AC 50/60 Hz<br>1.5 kW at 400/415 V AC 50/60 Hz<br>0.75 kW at 220/230 V AC 50/60 Hz |
| Thermal protection adjustment range | 2.5...4 A                                                                                          |
| [Uc] control circuit voltage        | 230 V AC 50/60 Hz                                                                                  |
| Control type                        | Selector switch 2 positions start black I-II<br>Pushbutton stop black O                            |

## Complementary

|                    |                                                                                 |
|--------------------|---------------------------------------------------------------------------------|
| Cable entry number | 4 cable entry :2 Pg 13 + 2 Pg 16 bottom<br>4 cable entry :2 Pg 13 + 2 Pg 16 top |
| Width              | 175 mm                                                                          |
| Height             | 165 mm                                                                          |
| Depth              | 146 mm                                                                          |
| Product weight     | 1.64 kg                                                                         |

## Environment

|                         |                                            |
|-------------------------|--------------------------------------------|
| Standards               | IEC 60204-1<br>IEC 60947-4-1               |
| Material                | Polycarbonate                              |
| IP degree of protection | IP55 for enclosure conforming to IEC 60529 |
| IK degree of protection | IK07 conforming to IEC 60529               |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.