Product data sheet Characteristics

LJ7K09Q714A39

TeSys LJ - enclosed DOL starter - 6...10 A - 24 V AC coil - no emergency stop



Main

Range of product	TeSys
Product name	LJ
Device short name	LJ7K
Product or component type	Enclosed DOL starter
Device application	Safety
Utilisation category	AC-3
Device composition	Control transformer Circuit-breaker Contactor
Motor power kW	4 kW at 380/400 V AC 50 Hz
Thermal protection adjustment range	610 A
[Uc] control circuit voltage	24 V AC 50/60 Hz
Control type	Pushbutton stop black O Pushbutton start white I

Complementary

Cable entry number	4 cable entry :2 Pg 13 + 2 Pg 16 bottom 4 cable entry :2 Pg 13 + 2 Pg 16 top	
Width	175 mm	
Height	165 mm	
Depth	146 mm	
Product weight	2.27 kg	

Environment

Standards	IEC 60204-1 IEC 60947-4-1	
Material	Polycarbonate	
IP degree of protection	IP55 conforming to IEC 60529	
IK degree of protection	IK07 conforming to IEC 60529	

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0844 - Schneider Electric declaration of conformity
Product end of life instructions	Need no specific recycling operations